



## Wedge Anchor

### Load Capacity - Ceiling Mounted/Concrete

306 kg	497 kg	692 kg	830 kg	1 987 kg
--------	--------	--------	--------	----------

### Load Capacity - Wall Mounted/Concrete

294 kg	489 kg	857 kg	1 349 kg	1 987 kg
--------	--------	--------	----------	----------

### Diameter

1/4 in	3/8 in	1/2 in	5/8 in	3/4 in
--------	--------	--------	--------	--------

### Thread Length

1/2 in	3/4 in	1 in	1 1/4 in	1 1/2 in
1 3/4 in	2 in	2 1/4 in	2 1/2 in	3 1/4 in
3 1/2 in	Min. 3 1/2 in	4 in	4 1/4 in	4 1/2 in
5 in	5 3/4 in	6 in	6 1/2 in	8 in

### Finish

Hot Deep Galvanized	Zinc	Zinc
---------------------	------	------

### Length

1 3/4 in	2 1/4 in	2 3/4 in	3 in	3 1/4 in
3 1/2 in	3 3/4 in	4 1/4 in	4 1/2 in	5 in
5 1/2 in	6 in	7 in	8 1/2 in	10 in

### Minimum Embedment

1-1/8"	1-5/8"	2-1/4"	2-3/4"	3-15/16"
--------	--------	--------	--------	----------

### Shear Point

11900 lb.	11 900 lbs	17523 lb.	2600 lb.	4320 lb.
7560 lb.				

### Tensile

10184 lb.* maximum	2700 lb.* maximum	4390 lb.* maximum	6110 lb.* maximum	7320 lb.* maximum
--------------------	-------------------	-------------------	-------------------	-------------------

### Packaging format

Blister of 2 units	Blister of 3 units	Blister of 4 units	Box of 10	Box of 10
			Box of 15	Box of 15
Box of 20	Box of 20	Box of 25	Box of 25	Box of 40
Box of 50	Box of 50	Box of 60	Box of 65	Box of 80
Box of 100	Box of 100	Box of 150	Box of 150	Box of 200
Box of 200	Box of 250	Box of 250	Box of 300	Box of 300
Box of 400	Box of 400	Box of 500	Box of 1000	Box of 1000

### DESCRIPTION

Top performance concrete anchors.  
High pullout resistance.

### AVAILABLE PRODUCTS

Product #	Load Capacity - Ceiling Mounted/Concrete	Load Capacity - Wall Mounted/Concrete	Diameter	Thread Length	Finish	Length	Minimum Embedment	Shear Point	Tensile	Packaging format
<b>WAHDG14134CT</b>	306 kg	294 kg	1/4 in	1/2 in	Hot Deep Galvanized	1 3/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 50
<b>WAZ14134MR</b>	306 kg	294 kg	1/4 in	1/2 in	Zinc	1 3/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Blister of 3 units
<b>WAZ14134CT</b>	306 kg	294 kg	1/4 in	1/2 in	Zinc	1 3/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 50
<b>WAZ14134</b>	306 kg	294 kg	1/4 in	1/2 in	Zinc	1 3/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 1000
<b>WAHDG14214CT</b>	306 kg	294 kg	1/4 in	1 in	Hot Deep Galvanized	2 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 50
<b>WAHDG14214</b>	306 kg	294 kg	1/4 in	1 in	Hot Deep Galvanized	2 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 1000
<b>WAZ14214J</b>	306 kg	294 kg	1/4 in	1 in	Zinc	2 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 50
<b>WAZ14214</b>	306 kg	294 kg	1/4 in	1 in	Zinc	2 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 1000
<b>WAZ14214CT</b>	306 kg	294 kg	1/4 in	1 in	Zinc	2 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 50
<b>WAZ143MR</b>	306 kg	294 kg	1/4 in	1 3/4 in	Zinc	3 in	1-1/8"	2600 lb.	2700 lb.* maximum	Blister of 2 units
<b>WAZ143J</b>	306 kg	294 kg	1/4 in	1 3/4 in	Zinc	3 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 50
<b>WAZ14314CT</b>	306 kg	294 kg	1/4 in	2 in	Zinc	3 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 50
<b>WAZ14314</b>	306 kg	294 kg	1/4 in	2 in	Zinc	3 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 500
<b>WAZ14214VA</b>	306 kg	294 kg	1/4 in	1 in	Zinc	2 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Box of 25
<b>WAZ14214MK</b>	306 kg	294 kg	1/4 in	2 1/4 in	Zinc	2 1/4 in	1-1/8"	2600 lb.	2700 lb.* maximum	Blister of 4 units
<b>WAHDG38214CT</b>	497 kg	489 kg	3/8 in	1/2 in	Hot Deep Galvanized	2 1/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25

Product #	Load Capacity - Ceiling Mounted/Concrete	Load Capacity - Wall Mounted/Concrete	Diameter	Thread Length	Finish	Length	Minimum Embedment	Shear Point	Tensile	Packaging format
<b>WAZ38214J</b>	497 kg	489 kg	3/8 in	1/2 in	Zinc	2 1/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAZ38214</b>	497 kg	489 kg	3/8 in	1/2 in	Zinc	2 1/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 500
<b>WAHDG38234</b>	497 kg	489 kg	3/8 in	1 in	Hot Deep Galvanized	2 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 400
<b>WAZ38234MK</b>	497 kg	489 kg	3/8 in	1 in	Zinc	2 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Blister of 2 units
<b>WAZ38234VA</b>	497 kg	489 kg	3/8 in	1 in	Zinc	2 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 15
<b>WAZ38234CT</b>	497 kg	489 kg	3/8 in	1 in	Zinc	2 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAZ38234J</b>	497 kg	489 kg	3/8 in	1 in	Zinc	2 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAZ38234</b>	497 kg	489 kg	3/8 in	1 in	Zinc	2 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 400
<b>WAZ383</b>	497 kg	489 kg	3/8 in	1 1/4 in	Zinc	3 in	1-1/8"	4320 lb.	4390 lb.* maximum	Box of 250
<b>WAZ383CT</b>	497 kg	489 kg	3/8 in	1 1/4 in	Zinc	3 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAHDG38334CT</b>	497 kg	489 kg	3/8 in	2 in	Hot Deep Galvanized	3 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAHDG38334</b>	497 kg	489 kg	3/8 in	2 in	Hot Deep Galvanized	3 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 300
<b>WAZ38334MK</b>	497 kg	489 kg	3/8 in	2 in	Zinc	3 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Blister of 2 units
<b>WAZ38334VA</b>	497 kg	489 kg	3/8 in	2 in	Zinc	3 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 15
<b>WAZ38334J</b>	497 kg	489 kg	3/8 in	2 in	Zinc	3 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAZ38334</b>	497 kg	489 kg	3/8 in	2 in	Zinc	3 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 300
<b>WAHDG385CT</b>	497 kg	489 kg	3/8 in	3 1/4 in	Hot Deep Galvanized	5 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 15
<b>WAHDG385</b>	497 kg	489 kg	3/8 in	3 1/4 in	Hot Deep Galvanized	5 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 250
<b>WAZ385MK</b>	497 kg	489 kg	3/8 in	3 1/4 in	Zinc	5 in	1-5/8"	4320 lb.	4390 lb.* maximum	Blister of 2 units
<b>WAZ385CT</b>	497 kg	489 kg	3/8 in	3 1/4 in	Zinc	5 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 15
<b>WAZ385J</b>	497 kg	489 kg	3/8 in	3 1/4 in	Zinc	5 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 15
<b>WAZ385</b>	497 kg	489 kg	3/8 in	3 1/4 in	Zinc	5 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 250
<b>WAHDG38234CT</b>	497 kg	489 kg	3/8 in	1 in	Hot Deep Galvanized	2 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAZ38334CT</b>	497 kg	489 kg	3/8 in	2 in	Zinc	3 3/4 in	1-5/8"	4320 lb.	4390 lb.* maximum	Box of 25
<b>WAHDG12234CT</b>	692 kg	857 kg	1/2 in	3/4 in	Hot Deep Galvanized	2 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 25
<b>WAHDG12234</b>	692 kg	857 kg	1/2 in	3/4 in	Hot Deep Galvanized	2 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 200

Product #	Load Capacity - Ceiling Mounted/Concrete	Load Capacity - Wall Mounted/Concrete	Diameter	Thread Length	Finish	Length	Minimum Embedment	Shear Point	Tensile	Packaging format
<b>WAZ12234CT</b>	692 kg	857 kg	1/2 in	3/4 in	Zinc	2 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 25
<b>WAZ12234J</b>	692 kg	857 kg	1/2 in	3/4 in	Zinc	2 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 25
<b>WAZ12234</b>	692 kg	857 kg	1/2 in	3/4 in	Zinc	2 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 200
<b>WAHDG12334CT</b>	692 kg	857 kg	1/2 in	1 3/4 in	Hot Deep Galvanized	3 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 20
<b>WAHDG12334</b>	692 kg	857 kg	1/2 in	1 3/4 in	Hot Deep Galvanized	3 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 150
<b>WAZ12334MK</b>	692 kg	857 kg	1/2 in	1 3/4 in	Zinc	3 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Blister of 2 units
<b>WAZ12334VA</b>	692 kg	857 kg	1/2 in	1 3/4 in	Zinc	3 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 10
<b>WAZ12334CT</b>	692 kg	857 kg	1/2 in	1 3/4 in	Zinc	3 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 20
<b>WAZ12334J</b>	692 kg	857 kg	1/2 in	1 3/4 in	Zinc	3 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 25
<b>WAZ12334</b>	692 kg	857 kg	1/2 in	1 3/4 in	Zinc	3 3/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 150
<b>WAHDG12414CT</b>	692 kg	857 kg	1/2 in	2 1/4 in	Hot Deep Galvanized	4 1/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAHDG12414</b>	692 kg	857 kg	1/2 in	2 1/4 in	Hot Deep Galvanized	4 1/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 150
<b>WAZ12414MK</b>	692 kg	857 kg	1/2 in	2 1/4 in	Zinc	4 1/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Blister of 2 units
<b>WAZ12414VA</b>	692 kg	857 kg	1/2 in	2 1/4 in	Zinc	4 1/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 10
<b>WAZ12414CT</b>	692 kg	857 kg	1/2 in	2 1/4 in	Zinc	4 1/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ12414J</b>	692 kg	857 kg	1/2 in	2 1/4 in	Zinc	4 1/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ12414</b>	692 kg	857 kg	1/2 in	2 1/4 in	Zinc	4 1/4 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 150
<b>WAHDG12512CT</b>	692 kg	857 kg	1/2 in	3 1/2 in	Hot Deep Galvanized	5 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAHDG12512J</b>	692 kg	857 kg	1/2 in	3 1/2 in	Hot Deep Galvanized	5 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAHDG12512</b>	692 kg	857 kg	1/2 in	3 1/2 in	Hot Deep Galvanized	5 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAZ12512CT</b>	692 kg	857 kg	1/2 in	3 1/2 in	Zinc	5 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ12512J</b>	692 kg	857 kg	1/2 in	3 1/2 in	Zinc	5 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ12512</b>	692 kg	857 kg	1/2 in	3 1/2 in	Zinc	5 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAHDG126CT</b>	692 kg	857 kg	1/2 in	4 in	Hot Deep Galvanized	6 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ126MK</b>	692 kg	857 kg	1/2 in	4 in	Zinc	6 in	2-1/4"	7560 lb.	6110 lb.* maximum	Blister of 2 units
<b>WAZ126CT</b>	692 kg	857 kg	1/2 in	4 in	Zinc	6 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15

Product #	Load Capacity - Ceiling Mounted/Concrete	Load Capacity - Wall Mounted/Concrete	Diameter	Thread Length	Finish	Length	Minimum Embedment	Shear Point	Tensile	Packaging format
<b>WAZ126</b>	692 kg	857 kg	1/2 in	4 in	Zinc	6 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAHDG127CT</b>	692 kg	857 kg	1/2 in	5 in	Hot Deep Galvanized	7 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ127CT</b>	692 kg	857 kg	1/2 in	5 in	Zinc	7 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ127</b>	692 kg	857 kg	1/2 in	5 in	Zinc	7 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAHDG12812CT</b>	692 kg	857 kg	1/2 in	6 1/2 in	Hot Deep Galvanized	8 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAHDG12812</b>	692 kg	857 kg	1/2 in	6 1/2 in	Hot Deep Galvanized	8 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAZ12812CT</b>	692 kg	857 kg	1/2 in	6 1/2 in	Zinc	8 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ12812</b>	692 kg	857 kg	1/2 in	6 1/2 in	Zinc	8 1/2 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAHDG1210CT</b>	692 kg	857 kg	1/2 in	8 in	Hot Deep Galvanized	10 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ1210CT</b>	692 kg	857 kg	1/2 in	8 in	Zinc	10 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 15
<b>WAZ1210</b>	692 kg	857 kg	1/2 in	8 in	Zinc	10 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 60
<b>WAHDG126</b>	692 kg	857 kg	1/2 in	4 in	Hot Deep Galvanized	6 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAHDG127</b>	692 kg	857 kg	1/2 in	5 in	Hot Deep Galvanized	7 in	2-1/4"	7560 lb.	6110 lb.* maximum	Box of 100
<b>WAHDG58312CT</b>	830 kg	1 349 kg	5/8 in	1 in	Hot Deep Galvanized	3 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAHDG58312</b>	830 kg	1 349 kg	5/8 in	1 in	Hot Deep Galvanized	3 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 100
<b>WAHDG58412CT</b>	830 kg	1 349 kg	5/8 in	2 in	Hot Deep Galvanized	4 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAZ58412CT</b>	830 kg	1 349 kg	5/8 in	2 in	Zinc	4 1/2 in	2-3/4"	11 900 lbs	7320 lb.* maximum	Box of 15
<b>WAZ58412MK</b>	830 kg	1 349 kg	5/8 in	2 in	Zinc	4 1/2 in	2-3/4"	11 900 lbs	7320 lb.* maximum	Blister of 2 units
<b>WAHDG585CT</b>	830 kg	1 349 kg	5/8 in	2 1/2 in	Hot Deep Galvanized	5 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAHDG585</b>	830 kg	1 349 kg	5/8 in	2 1/2 in	Hot Deep Galvanized	5 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 100
<b>WAZ586MK</b>	830 kg	1 349 kg	5/8 in	3 1/2 in	Zinc	6 in	2-3/4"	11 900 lbs	7320 lb.* maximum	Blister of 2 units
<b>WAZ586CT</b>	830 kg	1 349 kg	5/8 in	Min. 3 1/2 in	Zinc	6 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAZ587CT</b>	830 kg	1 349 kg	5/8 in	4 1/2 in	Zinc	7 in	2-3/4"	11 900 lbs	7320 lb.* maximum	Box of 10
<b>WAZ58312CT</b>	830 kg	1 349 kg	5/8 in	1 in	Zinc	3 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAZ58312</b>	830 kg	1 349 kg	5/8 in	1 in	Zinc	3 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 100

Product #	Load Capacity - Ceiling Mounted/Concrete	Load Capacity - Wall Mounted/Concrete	Diameter	Thread Length	Finish	Length	Minimum Embedment	Shear Point	Tensile	Packaging format
<b>WAHDG58412</b>	830 kg	1 349 kg	5/8 in	2 in	Hot Deep Galvanized	4 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 100
<b>WAZ58412J</b>	830 kg	1 349 kg	5/8 in	2 in	Zinc	4 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAZ58412</b>	830 kg	1 349 kg	5/8 in	2 in	Zinc	4 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 100
<b>WAZ585CT</b>	830 kg	1 349 kg	5/8 in	2 1/2 in	Zinc	5 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAZ585</b>	830 kg	1 349 kg	5/8 in	2 1/2 in	Zinc	5 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 100
<b>WAHDG586CT</b>	830 kg	1 349 kg	5/8 in	3 1/2 in	Hot Deep Galvanized	6 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 10
<b>WAZ586</b>	830 kg	1 349 kg	5/8 in	3 1/2 in	Zinc	6 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 50
<b>WAHDG587CT</b>	830 kg	1 349 kg	5/8 in	4 1/2 in	Hot Deep Galvanized	7 in	2-3/4"	11 900 lbs	7320 lb.* maximum	Box of 10
<b>WAZ587</b>	830 kg	1 349 kg	5/8 in	4 1/2 in	Zinc	7 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 80
<b>WAHDG58812CT</b>	830 kg	1 349 kg	5/8 in	6 in	Hot Deep Galvanized	8 1/2 in	2-3/4"	11 900 lbs	7320 lb.* maximum	Box of 10
<b>WAZ58812</b>	830 kg	1 349 kg	5/8 in	6 in	Zinc	8 1/2 in	2-3/4"	11900 lb.	7320 lb.* maximum	Box of 50
<b>WAZ58812CT</b>	830 kg	1 349 kg	5/8 in	6 in	Zinc	8 1/2 in	2-3/4"	11 900 lbs	7320 lb.* maximum	Box of 10
<b>WAZ34414CT</b>	1 987 kg	1 987 kg	3/4 in	1 1/2 in	Zinc	4 1/4 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 15
<b>WAZ34414</b>	1 987 kg	1 987 kg	3/4 in	1 1/2 in	Zinc	4 1/4 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 65
<b>WAHDG346</b>	1 987 kg	1 987 kg	3/4 in	3 1/4 in	Hot Deep Galvanized	6 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 50
<b>WAZ346CT</b>	1 987 kg	1 987 kg	3/4 in	3 1/4 in	Zinc	6 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 10
<b>WAZ346</b>	1 987 kg	1 987 kg	3/4 in	3 1/4 in	Zinc	6 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 50
<b>WAZ347</b>	1 987 kg	1 987 kg	3/4 in	4 1/4 in	Zinc	7 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 50
<b>WAZ34812</b>	1 987 kg	1 987 kg	3/4 in	5 3/4 in	Zinc	8 1/2 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 40
<b>WAHDG346CT</b>	1 987 kg	1 987 kg	3/4 in	3 1/4 in	Hot Deep Galvanized	6 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 10
<b>WAHDG347CT</b>	1 987 kg	1 987 kg	3/4 in	4 1/4 in	Hot Deep Galvanized	7 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 10
<b>WAZ347CT</b>	1 987 kg	1 987 kg	3/4 in	4 1/4 in	Zinc	7 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 10

Product #	Load Capacity - Ceiling Mounted/Concrete	Load Capacity - Wall Mounted/Concrete	Diameter	Thread Length	Finish	Length	Minimum Embedment	Shear Point	Tensile	Packaging format
<b>WAZ34812CT</b>	1 987 kg	1 987 kg	3/4 in	5 3/4 in	Zinc	8 1/2 in	3-15/16"	17523 lb.	10184 lb.* maximum	Box of 10

## TECHNICAL SPECIFICATIONS

<b>Mounting Location</b>	Wall, Ceiling
<b>Compatible Materials</b>	Concrete
<b>Material</b>	Steel

## IMPORTANT INFORMATION

\* As a safety factor, industry standards recommend using 25% of the ultimate load. Ultimate load in 4000 PSI concrete.

## APPLICATION

The use of a hammer drill is best suited for drilling holes in concrete.

## PRODUCT PHOTOS

