



Hollow Wall Anchor

Diameter

1/8 in

3/16 in

Length

1 in

1 1/4 in

2 in

2 1/4 in

3 in

Packaging format

Blister of 6
units

Blister of 8
units

Blister of 10
units

Blister of 12
units

Box of 1000

Box of 1200

Box of 1500

Box of 3000

Box of 5000

DESCRIPTION

Metal anchors for hollow walls

For 5/8 in (15.88 mm) to 1 in (25.4 mm) thick walls.
This anchor requires pre-drilling.

AVAILABLE PRODUCTS

Product #	Diameter	Length	Packaging format
HWA18XSMK	1/8 in	1 in	Blister of 12 units
HWA18XS	1/8 in	1 in	Box of 5000
HWA18SMK	1/8 in	1 1/4 in	Blister of 10 units
HWA18S	1/8 in	1 1/4 in	Box of 3000
HWA18LMK	1/8 in	2 1/4 in	Blister of 10 units
HWA18L	1/8 in	2 1/4 in	Box of 1500
HWA316SMK	3/16 in	2 in	Blister of 8 units
HWA316S	3/16 in	2 in	Box of 1000
HWA316LMK	3/16 in	3 in	Blister of 6 units
HWA316L	3/16 in	3 in	Box of 1200

TECHNICAL SPECIFICATIONS

Compatible Materials	Drywall
Finish	Zinc
Load Capacity - Wall Mounted/Drywall	36 kg

APPLICATION

- Drywall

PRODUCT PHOTOS

