



## Concrete Drill Bit

### Shank Diameter

5/32 in

3/16 in

1/4 in

### Bit Length (L)

1/2 in

3 1/2 in

4 in

4 1/2 in

5 1/2 in

6 1/2 in

### Packaging format

Per unit

Blister

Blister of 5  
units

Blister of 10  
units

## DESCRIPTION

Drill bit with carbide tipped blade for masonry (brick, block, concrete). Can be used with regular drills or hammer drills. Ensures precise drilling in concrete and other masonry products.

## AVAILABLE PRODUCTS

| Product #           | Shank Diameter | Bit Length (L) | Packaging format    |
|---------------------|----------------|----------------|---------------------|
| <b>TMD532312N</b>   | 5/32 in        | 3 1/2 in       | Per unit            |
| <b>TMD532312NMK</b> | 5/32 in        | 3 1/2 in       | Blister of 5 units  |
| <b>TMD532312PK</b>  | 5/32 in        | 3 1/2 in       | Blister of 10 units |
| <b>TMD532412N</b>   | 5/32 in        | 4 1/2 in       | Per unit            |
| <b>TMD532412PK</b>  | 5/32 in        | 4 1/2 in       | Blister of 10 units |
| <b>TMD532512N</b>   | 5/32 in        | 5 1/2 in       | Per unit            |
| <b>TMD532512MR</b>  | 5/32 in        | 5 1/2 in       | Blister             |
| <b>TMD532512NMK</b> | 5/32 in        | 5 1/2 in       | Blister of 5 units  |
| <b>TMD532512PK</b>  | 5/32 in        | 5 1/2 in       | Blister of 10 units |
| <b>TMD316312N</b>   | 3/16 in        | 3 1/2 in       | Per unit            |
| <b>TMD316312NMK</b> | 3/16 in        | 3 1/2 in       | Blister of 5 units  |
| <b>TMD316312PK</b>  | 3/16 in        | 3 1/2 in       | Blister of 10 units |
| <b>TMD316412N</b>   | 3/16 in        | 4 1/2 in       | Per unit            |
| <b>TMD316412PK</b>  | 3/16 in        | 4 1/2 in       | Blister of 10 units |
| <b>TMD316512MR</b>  | 3/16 in        | 5 1/2 in       | Blister             |
| <b>TMD316512NMK</b> | 3/16 in        | 5 1/2 in       | Blister of 5 units  |
| <b>TMD316512PK</b>  | 3/16 in        | 5 1/2 in       | Blister of 10 units |
| <b>TMD316612PK</b>  | 3/16 in        | 6 1/2 in       | Blister of 10 units |
| <b>TMD316612N</b>   | 3/16 in        | 1/2 in         | Per unit            |
| <b>TMD316512N</b>   | 3/16 in        | 5 1/2 in       | Per unit            |
| <b>TMDN144</b>      | 1/4 in         | 4 in           | Per unit            |

## TECHNICAL SPECIFICATIONS

|              |          |
|--------------|----------|
| <b>Brand</b> | Reliable |
|--------------|----------|

## APPLICATION

3/16 in (4.76 mm) bit is suitable for the installation of 1/4 in (6.35 mm) concrete screws. 5/32 in (3.97 mm) bit is suitable for the installation of 3/16 in (4.76 mm) concrete screws.

## PRODUCT PHOTOS

---

