



## Wedge Concrete Anchor, Hex Head with Washer and Serration

### Screw Size

1/2	1/4	3/8
-----	-----	-----

### Length

2 1/4 in	3 in	4 in
----------	------	------

### Bit Dimensions

1/2	1/4	3/8
-----	-----	-----

### Thread Count (Pitch/TPI)

2.5	3	4
-----	---	---

### Packaging format

Blister of 4 units	Box of 20	Box of 100	Box of 150	Box of 250
	Box of 300	Box of 1000		

## DESCRIPTION

The Gator Bolt XXL, heavy-duty concrete screw fastener is a new generation of product for the construction market. The Gator Bolt XXL is a large diameter anchor with considerable pull-out values, tough corrosion resistance, simple to install, and the only large diameter concrete anchor that is also easy to remove.

## ADVANTAGES AND BENEFITS

- Provides an alternative to typical wedge or sleeve with the benefit of a nicer fit and finish.
- Grips concrete without using compression; ideal for crack concrete situations or use near an edge, where wedges or sleeves cannot be used.
- Easy to remove (ideal for construction site safety railings).
- Length and size head markings allow for easy on-site inspection.
- Silver-Chem finish provides exceptional corrosion resistance and ACQ resistance (pressure treated wood chemical).
- Locking serrations under the head prevent back-out and increase resistance to vibration.
- Top strength: high pull-out and shear values.
- Low torque installation.
- Installs using standard ANSI masonry drill bits.

## AVAILABLE PRODUCTS

Product #	Screw Size	Length	Bit Dimensions	Thread Count (Pitch/TPI)	Packaging format
WABHDG123MX	1/2	3 in	1/2	2.5	Blister of 4 units
WABHDG123CT	1/2	3 in	1/2	2.5	Box of 20
WABHDG123	1/2	3 in	1/2	2.5	Box of 150
WABHDG124MX	1/2	4 in	1/2	2.5	Blister of 4 units
WABHDG124CT	1/2	4 in	1/2	2.5	Box of 20
WABHDG124	1/2	4 in	1/2	2.5	Box of 100
WABHDG14214	1/4	2 1/4 in	1/4	4	Box of 1000
WABHDG383MX	3/8	3 in	3/8	3	Blister of 4 units
WABHDG383CT	3/8	3 in	3/8	3	Box of 20
WABHDG383	3/8	3 in	3/8	3	Box of 300
WABHDG384MX	3/8	4 in	3/8	3	Blister of 4 units
WABHDG384CT	3/8	4 in	3/8	3	Box of 20
WABHDG384	3/8	4 in	3/8	3	Box of 250

## TECHNICAL SPECIFICATIONS

Drive required	Hex
Finish	Hot-Dip Galvanized
Head Type	Hexagon with Washer and Serration
Point Type	Blunt
Brand	Gator Bolt XXL
Threading	Full thread
Concrete Drill Bit Included	Not Included
Minimum Hole Depth	2"
Minimum Insertion	2 in
Specific Application	Concrete
Standards and Certifications	ACQ Treatment
Material	Hot-Dip Galvanized Steel

## APPLICATION

- Safety railings and equipment on construction sites - Balcony railings - Warehouse racking and garage shelving - Accordion and pull-down shutter tracks - Impact-resistant window systems

## IMPORTANT INFORMATION

PLEASE NOTE \*You must drill a hole 1 in (25.4 mm) deeper than the insertion intended.\*

## PRODUCT PHOTOS

