



Roof Metal Screw, Hex Head with Steel and Neoprene Washer, Self-Tapping Thread, Type A Point

Screw Size

14

9

Length

1 in

1 1/2 in

2 in

2 1/2 in

Metal Screw Thread Count (PITCH/TPI)

10

15

Head Size

6.35 mm
(1/4")

9.5 mm (3/8")

Drive Size

1/4" (Hex)

3/8" (Hex)

Thread Count (Pitch/TPI)

10

15

Packaging format

Blister of 3
units

Blister of 5
units

Blister of 6
units

Box of 100

Box of 200

Box of 300

Box of 400

Box of 500

Bag of 500
units

DESCRIPTION

Complete your roofing projects with these roof screws. The steel screws feature a Dacrotized coating that provides exceptional corrosion resistance and have been tested for 1000 hours of salt spray for superior performance. They feature a hex head with a steel and neoprene washer that provides a tight seal. The sharp Type A point and self-tapping thread ensures these roofing screws offer a firm hold and smooth penetration.

*Tested for 1000 hours of salt spray.

AVAILABLE PRODUCTS

Product #	Screw Size	Length	Metal Screw Thread Count (PITCH/TPI)	Head Size	Drive Size	Thread Count (Pitch/TPI)	Packaging format
RSZ14112MR	14	1 1/2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Blister of 3 units
RSZ14112VP	14	1 1/2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Box of 100
RSZ14112J	14	1 1/2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Box of 300
RSZ14112	14	1 1/2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Bag of 500 units
RSZ142MR	14	2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Blister of 3 units
RSZ142VP	14	2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Box of 100
RSZ142J	14	2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Box of 200
RSZ142	14	2 in	10	9.5 mm (3/8")	3/8" (Hex)	10	Bag of 500 units
RSZ91MR	9	1 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Blister of 6 units
RSZ91VP	9	1 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Box of 100
RSZ91J	9	1 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Box of 400
RSZ91	9	1 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Bag of 500 units
RSZ9112MR	9	1 1/2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Blister of 5 units
RSZ9112VP	9	1 1/2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Box of 100
RSZ9112J	9	1 1/2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Box of 500
RSZ9112	9	1 1/2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Bag of 500 units
RSZ92MR	9	2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Blister of 5 units
RSZ92VP	9	2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Box of 100
RSZ92J	9	2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Box of 400
RSZ92	9	2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Bag of 500 units
RSZ9212	9	2 1/2 in	15	6.35 mm (1/4")	1/4" (Hex)	15	Bag of 500 units

TECHNICAL SPECIFICATIONS

Drive required	Hex
Finish	Dacrotized
Head Type	Hexagon with Steel and Neoprene Washer
Thread Type	Self-Tapping
Point Type	Type A
Brand	Reliable
Threading	Full thread
Specific Application	Roof
Standards and Certifications	Not Certified
Material	Steel

PRODUCT PHOTOS

