



Knurled Drop-in Anchor

Load Capacity - Ceiling Mounted/Concrete

275 lb	525 lb	1 000 lb	2 000 lb
--------	--------	----------	----------

Load Capacity - Wall Mounted/Concrete

525 lb	1 100 lb	1 550 lb	3 850 lb
--------	----------	----------	----------

Diameter

3/8 in	1/2 in	5/8 in	1 in
--------	--------	--------	------

Thread Length

7/16 in	5/8 in	3/4 in	1 1/4 in
---------	--------	--------	----------

Drill Bit

3/8 in	1/2 in	5/8 in	1 in
--------	--------	--------	------

Bolt Size

1/4 in	3/8 in	1/2 in	3/4 in
--------	--------	--------	--------

Length

1 in	1 1/2 in	2 in	3 1/8 in
------	----------	------	----------

Minimum Embedment

1-1/2"	2	25.4 mm (1")	38 mm (3-1/4")
--------	---	--------------	----------------

Thread Count (Pitch/TPI)

10	13	16	20
----	----	----	----

Packaging format

Box of 20	Box of 25	Box of 50	Box of 100
-----------	-----------	-----------	------------

DESCRIPTION

DPZ

AVAILABLE PRODUCTS

Product #	Load Capacity - Ceiling Mounted/Concrete	Load Capacity - Wall Mounted/Concrete	Diameter	Thread Length	Drill Bit	Bolt Size	Length	Minimum Embedment	Thread Count (Pitch/TPI)	Packaging format
DPZ14CT	275 lb	525 lb	3/8 in	7/16 in	3/8 in	1/4 in	1 in	25.4 mm (1")	20	Box of 100
DPZ38CT	525 lb	1 100 lb	1/2 in	5/8 in	1/2 in	3/8 in	1 1/2 in	1-1/2"	16	Box of 50
DPZ12CT	1 000 lb	1 550 lb	5/8 in	3/4 in	5/8 in	1/2 in	2 in	2	13	Box of 25
DPZ34CT	2 000 lb	3 850 lb	1 in	1 1/4 in	1 in	3/4 in	3 1/8 in	38 mm (3-1/4")	10	Box of 20

TECHNICAL SPECIFICATIONS

Mounting Location	Wall, Ceiling
Compatible Materials	Concrete, Block, Brick
Finish	Zinc
Brand	Reliable
Specific Application	Concrete
Material	Steel

PRODUCT PHOTOS

