



PWR DRIVE STR - Structural framing screw

Screw Size

3/8

5/16

Length

3 in

4 1/2 in

6 in

6 1/2 in

8 1/2 in

Packaging format

Blister of 10
units

Box of 50

Box of 125

Box of 150

Box of 200

Box of 250

Box of 400

DESCRIPTION

Ideal for deck structure assemblies

The PWR DRIVE STR is designed to replace lag screws for framing decks or to alleviate the need for standard #10 deck screws leading to potential structural problems. The design of the STR is specific to dimensional lumber used in deck structures and pretty much any other framing needs for that matter, which allows maximum assembly strength.

By figuring out all the possible assemblies of a structure, using a mix of 2 x 6 in (152 mm), 2 x 8 in (203 mm), 2 x 10 in (254 mm), 4 x 4 in (101.6 mm), and 6 x 6 in (152 mm), you can cover all possible combinations with only five different lengths of the STR. Fewer screws are necessary to cover anything you may encounter on the jobsite.

Each pack of the STR includes a handy reference for the correct lumber combinations ideal for a specific length. Note that the required T-40 tip is included in each pack except in bulk.

ADVANTAGES AND BENEFITS

- Specific thread lengths for more strength - New sticky T-40 star drive - No pre-drilling: self-tapping thread and type 17 tip - Extra wide flat head with nibs for unparalleled fit and finish - Anti-friction "U" thread reduces friction on the shank, improving the performance of your tool's batteries - Brown sienna ACQ finish, perfect for pressure treated wood - Super strength, ease, and execution speed

AVAILABLE PRODUCTS

Product #	Screw Size	Length	Packaging format
FTC17BR38612MR	3/8	6 1/2 in	Blister of 10 units
FTC17BR38612L	3/8	6 1/2 in	Box of 50
FTC17BR38612	3/8	6 1/2 in	Box of 150
FTC17BR38812MR	3/8	8 1/2 in	Blister of 10 units
FTC17BR38812L	3/8	8 1/2 in	Box of 50
FTC17BR38812	3/8	8 1/2 in	Box of 125
FTC17BR5163MR	5/16	3 in	Blister of 10 units
FTC17BR5163L	5/16	3 in	Box of 50
FTC17BR5163	5/16	3 in	Box of 400
FTC17BR516412MR	5/16	4 1/2 in	Blister of 10 units
FTC17BR516412L	5/16	4 1/2 in	Box of 50
FTC17BR516412	5/16	4 1/2 in	Box of 250
FTC17BR5166MR	5/16	6 in	Blister of 10 units
FTC17BR5166L	5/16	6 in	Box of 50
FTC17BR5166	5/16	6 in	Box of 200

TECHNICAL SPECIFICATIONS

Standards and Certifications	ICC ES: ESR-4558
Brand	PWR DRIVE
Finish	ACQ Rustproof
Specific Application	Structure Assembly
Function	Deck Framing Structures
Steel Grade	Tempered
Head Type	Oversized Flat Head with Nibs
Drive required	T-40
Thread Type	Coarse
Point Type	Type 17
Threading	1-1/2" thread
Type of Wood	Lumber, Treated Wood

INCLUDED PRODUCT(S)

T40 bit is included in all packaging.

APPLICATION

Ideal for: - Deck framing - Timber - Posts and framework - Beam assemblies - Landscaping - And much more!

PRODUCT PHOTOS



